THE NEW & RECLAIMED FLOORING CO

www.reclaimedflooringco.com

sales@reclaimedflooringco.com

UK +44 (0) 207 250 1108

CASTLE: TUDOR

Pattern	Construction	Profile	Profile	Edge	Installation
Planks	Solid with surface undulation	Tongue and Groove	Soft Round or Hand Carved	Hard Wax Oil	Glue, Secret Nail

Solid

Overall Thickness	20-23mm
Width	185, 220mm
Length	600mm-2450mm / 80% of boards will be 1800mm+

N.B. Sizes may change at any time

Grading

Species	European Oak (Quercus Robur)
Top Layer	n/a
Base Layer	n/a
Grade	A/D
Maximum Open Knots	40mm
Maximum Size of Closed Knots	60mm
Filled Defects	Allowed
Sapwood	Traces permitted 60mm
End Checks	No longer than width of board allowed (max. 2mm open)
Filler	2 component solvent free filler with oak dust
Colour Variation	Medium
Filled Crack	Allowed

Tests

Euro Fire Classification	D3

Sustainability & Certifications

FSC and PEF	Timber Neutral	EUTR	LACEY ACT	Formaldehyde Emission
No	Yes	Legally Harvested	Legally Harvested	E1 (0.1ppm): complete compliance with EU safety standards

N.B. We plant 1 tree per every 10m² you buy. Certification comes as standard.

PEFC PEFC/16-37-1847 Promoting Sustainable Forest Management www.pefc.org

FSC www.fsc.org FSC® C109654 The mark of responsible forestry

nwfa National Wood Flooring Association

LACEY ACT COMPLIANT

CARB PHASE 2 COMPLIANT

timber neutral

Mouldings

Bull Nose	T Bar	Ramp	Stop End	Square Nosing
				

N.B. For a seamless transition, we can colour-match the selected moulding with this product.

Staircase



We offer the opportunity to customise stairs to complement or match our wood flooring.

1. Stairs and claddings are available in a variety of construction types and styles.
2. Stair material is available to match the majority of our wood floors.



3. We offer both contemporary and traditional nosing styles.
4. Stairs are either constructed using our finest engineered platforms or solid wood. Construction will vary depending on nosing types.



Guarantees

Lifetime Structural Guarantee:

The Company's warranty commitment is to provide the retail purchaser quality wood flooring that is free from structural defects in milling for the lifetime of the product, where products have been installed to our guidelines and the site conditions for temperature and humidity are met).

20-year Finish Guarantee:

The Company's products are covered under this 20 year finish warranty only when cleaned and maintained per the guidelines set forth for the product colour and coating.

In both cases please refer to the Warranty document received at the time of purchase for full guarantee details and exclusions.

© This technical data sheet was written by The Reclaimed Flooring Company Limited, UK. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.