

PRODUCT SPEC PAGE

Collection Name

Grande Restoration

We have always been a company that adores the way time alters and shapes the appearance wood, adding its own special patina over the centuries. Our challenge for this collection was to abbreviate this process while still retaining the classical grace that time lavishes. The most distinctive feature in this collection is the surface undulation typical of grand, ancient European floors. Drawing upon this beauty and tradition we have created the Grande Restoration collection to embody all of the elements of a truly luxurious oak floor. Small board cracks, select knots and occasional soft band saw marks are subtle variations exhibited in this timeless collection. Created with the concept of inheritance, two sub-ranges Castle and Habitat further expand and enrich the Grande Restoration collection in two distinct directions. Castle products play on the idea of inheriting history whereas the Habitat range focuses on inheriting something from the earth.



Product Name

Castle French Carriage

From - £115 + VAT

Product Information

|                   |                       |                              |                                                    |                        |                                      |                                            |                  |
|-------------------|-----------------------|------------------------------|----------------------------------------------------|------------------------|--------------------------------------|--------------------------------------------|------------------|
| Pattern<br>Planks | Construction<br>Solid | Profile<br>Tongue and Groove | Edge<br>Micro Bevel,<br>Soft Round,<br>Hand Carved | Finish<br>Hard Wax Oil | Installation<br>Glue and Secret Nail | Species<br>European Oak<br>(Quercus Robur) | Origin<br>Europe |
|-------------------|-----------------------|------------------------------|----------------------------------------------------|------------------------|--------------------------------------|--------------------------------------------|------------------|

Product Structure



Solid

Overall Thickness : 21mm-24mm  
Length :18.5cm, 22cm  
Width :1.5m-2.6m  
Where the 80% of the batch is above 2m  
Under Floor Heating :No

N.B. Sizes may change at any time

# Sustainability

|                                        |                       |                                  |                                                                                    |
|----------------------------------------|-----------------------|----------------------------------|------------------------------------------------------------------------------------|
| FSC and PEFC<br>Optional at extra cost | Timber Neutral<br>Yes | EUTR<br>Legally Harvested Timber | Formaldehyde Emission<br>E1 (0.1ppm): complete compliance with EU safety standards |
|----------------------------------------|-----------------------|----------------------------------|------------------------------------------------------------------------------------|

N.B. We plant 1 tree per every 10m2 you buy. Certification comes as standard.

# Grading

|                                                                   |
|-------------------------------------------------------------------|
| Grade : A-D                                                       |
| Maximum Open Filled Knot : Not Filled                             |
| Maximum Size of Knots : 8cm                                       |
| Filled Defects : Open Defects                                     |
| Sapwood : Allowed                                                 |
| End Checks : No Longer Than Width of Board Allowed (Max 3mm Open) |
| Filler : No Filler                                                |
| Colour Variation : Allowed                                        |
| Filled Crack : Not filled                                         |

N.B. The product grading criteria is an approximation. Please allow for vairants.

# Tests

|                                                   |
|---------------------------------------------------|
| Slip Testing (to BS 7976-2) : Wet: 29 / Dried: 64 |
| European reaction to fire classification : Cfl-s1 |

© This technical data sheet was written by The Reclaimed Flooring Company Limited, UK. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

**Central London, UK**  
64 Clerkenwell Road  
London, EC1M 5PX, UK  
+44 (0) 207 250 1108

**California, USA**  
www.reclaimedflooringco.us  
212 Marine Street, Suite 100  
Santa Monica, CA 90405  
+1 (424) 322-9200

**Trelleborg, Sweden**  
Värlinge Gamla Mejeri  
Värlingevägen 273-0, 231 94  
+46 40 685 06 80  
**Cheshire, UK**  
Unit 3 Hammond Trade Centre  
Hammond Avenue, Stockport  
Cheshire SK4 1PQ, UK  
+44 (0) 161 429 9284