PRODUCT SPEC PAGE

Collection Name

Painted Wood

Bullet proof like no other painted lne on the market. Made from distilled water using natural earth mineral pigmentations our Painted collection exhibits a vibrant and eclectic mix of colours suitable for commercial and residential use. Through vast experimentation, we have developed our own colour layering system that creates a highly weathered aesthetic without the decades wait.

Especially valuable for company branding we provide the personalisation of colour combinations allowing the client to choose a total bespoke look every time. A kaleidoscopic of colours and combinations make this an exciting and innovative collection full of fun and fascination.



Product Name

Double Colour Chipped or Weathered

From - £98 + VAT

Product Information

Pattern	
Planks	

Construction
Solid /
Engineered

Profile

Tongue and
Groove

Edge

Micro Bevel

Finish Metallic

Paint

Installation
Glue and Secret
Nail

Species European Oak (Quercus Robur) Origin Top Layer: Europe / Base Layer: Russia

Product Structure



Solid

Overall Thickness: 20mm

Length: 18,5cm, 22cm, 24cm, 28cm

Width: 0.6m-2.45m

Where the 80% of the bacth is above 1.8m

Under Floor Heating :No

Engineered



Overall Thickness: 21mm
Hardwood Layer:6mm
Birch Plywood Layer:15mm
Length:18,5cm, 22cm, 24cm, 28cm

Width: 0.6m-2.45m

Where the 80% of the bacth is above 1.8m

Under Floor Heating: Yes

Overall Thickness: 16mm
Hardwood Layer: 4mm
Birch Plywood Layer: 12mm
Length: 18,5cm, 22cm, 24cm, 28cm

Width :0.6m-2.45m

Where the 80% of the bacth is above 1.8m

Under Floor Heating :Yes

Engineered Flooring Guarantee

This manufacturing guarantee is for all of our European Engineered oak wood floors, which have been manufacturing using Water Proof Boiled Birch ply. This Guarantee is against de-lamination only which occurs in the 12 months following installation of the flooring. If de-lamination occurs during that period, The Reclaimed Flooring Company, upon inspection and verification that none of the criteria (please refer to the guarantee section in the website) in respect of non-application of the guarantee are applicable, will repair or replace the board or boards that have de-laminated.

No refunds of any kind will be given.

N.B. Sizes may change at any time

Sustainability

FSC and PEFC

Optional at extra cost

Timber Neutral

Yes

EUTR

Legally Harvested Timber

Formaldehyde Emission

E1 (0.1ppm): complete compliance with

EU safety standards

N.B. We plant 1 tree per every 10m2 you buy. Certification comes as standard.

Grading

Grade :	A-C
Maximum Open Filled Knot :	6cm
Maximum Size of Knots :	7,5cm
Filled Defects :	Allowed
Sapwood :	Traces Permitted
End Checks:	No Longer Than Width of Board Allowed (Max 2mm Open)
Filler:	2 component solvent free filler with oak dust
Colour Variation :	Allowed
Filled Crack :	Allowed

N.B. The product grading criteria is an approximation. Please allow for vairants.

Tests

Slip Testing (to BS 7976-2): Wet: 29 / Dried: 64

European reaction to fire classification: Cfl-s1

© This technical data sheet was written by The Reclaimed Flooring Company Limited, UK. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

Central London, UK

64 Clerkenwell Road London, EC1M 5PX, UK +44 (0) 207 250 1108

California, USA www.reclaimedflooringco.us 212 Marine Street, Suite 100 Santa Monica, CA 90405 +1 (424) 322-9200

Trelleborg, Sweden

Värlinge Gamla Mejeri Värlingevägen 273-0, 231 94 +46 40 685 06 80

Cheshire, UK

Unit 3 Hammond Trade Centre Hammond Avenue, Stockport Cheshire SK4 1PQ, UK +44 (0) 161 429 9284